



## Product Description

3M™ Thinsulate™ TK Acoustic Insulation is:

**Compressible** – fits a wide range of applications where varying thickness is highly desirable

**Conformable** – specifically designed to accommodate irregular spaces

**Cavity Filling** – fills voids behind trim panels or other areas to help reduce noise

3M™ Thinsulate™ TK is a high performance, low density material. Its acoustic and thermal properties make it ideal for use in a multitude of commercial vehicle applications.

MATERIAL	TK-2162	TK-2194	TK-2232	TK-2235	TK-2261	TK-2332	TK-2342	TK-2652
<b>Thickness (mm)</b>	16	13	27	27	16	25	41	50
<b>Material Facing</b>	White scrim on both sides	White Scrim / Aluminized Polyester	White scrim on both sides	White Scrim / Black Scrim	White Scrim / No Scrim	White scrim on both sides	White scrim on both sides	White scrim on both sides
<b>Areal Weight (GSM)</b>	160	195	230	255	260	330	340	650
<b>Normal Sound Absorption Avg. 250 - 2500 Hz (α)</b>	0.29	0.35	0.43	0.41	0.44	0.47	0.51	0.67
<b>Normal Sound Absorption Avg. 315 - 1600 Hz (α)</b>	0.16	0.25	0.33	0.31	0.36	0.39	0.52	0.74
<b>R Value at 20°C (ft<sup>2</sup>hr °F/BTU)</b>	2	2	3	3	2	3	6	7
<b>Maximum Continuous Operating Temperature, °C (°F)</b>	120 (248)	120 (248)	120 (248)	120 (248)	120 (248)	120 (248)	120 (248)	120 (248)
<b>Flammability (FMVSS-302)</b>	Meets	Meets	Meets	Meets	Meets	Meets	Meets	Meets
<b>Compressibility, Pa (lb/ft<sup>2</sup>)</b>								
10%	17 (0.3)	29 (0.6)	18 (0.4)	18 (0.4)	17 (0.3)	29 (0.6)	18 (0.4)	29 (0.6)
25%	49 (1.0)	57 (1.2)	59 (1.2)	59 (1.2)	49 (1.0)	62 (1.3)	64 (1.3)	67 (1.4)
50%	223 (4.6)	148 (3.1)	276 (5.8)	276 (5.8)	223 (4.6)	239 (5.0)	279 (5.8)	326 (6.8)

### Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that Aearo Technologies believes are reliable, but the accuracy or completeness of such information is not guaranteed.

### Product Use

Many factors beyond Aearo Technologies's control and uniquely within user's knowledge and control can affect the use and performance of a Aearo Technologies product in a particular application. Given the variety of factors that can affect the use and performance of an Aearo Technologies product, user is solely responsible for evaluating the Aearo Technologies product and determining whether it is fit for a particular purpose and suitable for user's method of application.

### Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable Aearo Technologies product packaging or product literature, Aearo Technologies warrants that each Aearo Technologies product meets the applicable Aearo Technologies product specification at the time Aearo Technologies ships the product. Aearo Technologies MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the Aearo Technologies product does not conform to this warranty, then the sole and exclusive remedy is, at Aearo Technologies's option, replacement of the Aearo Technologies product or refund of the purchase price.

### Limitation of Liability

Except where prohibited by law, Aearo Technologies will not be liable for any loss or damage arising from the Aearo Technologies product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

